

PT/GB2004/004229



INVESTOR IN PEOPLE

PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

REC'D 22 OCT 2004

WIPO

PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.


In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, L.C. or P.L.C.


Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Andrew Gersey

Dated 14 October 2004





100CT03 E843719-1 D02896
P01/7700.00-0323781.5

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

10 OCT 2003

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference

RAB.P04893GB

2. Patent application number

(The Patent Office will fill in this part)

0323781.5

3. Full name, address and postcode of the or of each applicant (underline all surnames)

Bodycage Limited
2 Market Place
Faringdon
Oxfordshire SN7 7HW

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

08434300002
Great Britain

4. Title of the invention

Safety Helmet

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Marks & Clerk
27 Imperial Square
Cheltenham
Gloucestershire GL50 1RQ
Great Britain

Patents ADP number (if you know it)

18014 ✓

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d)

Yes

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form.
Do not count copies of the same document

Continuation sheets of this form

Description 11

Claim(s) Nil

Abstract Nil

Drawing(s) 2 *PM*

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and search (*Patents Form 9/77*)

Request for substantive examination (*Patents Form 10/77*)

Any other documents
(*please specify*)

11. I/We request the grant of a patent on the basis of this application.

Signature

Mars & Cleve

Date 09.10.03

Agents for the Applicant

12. Name and daytime telephone number of person to contact in the United Kingdom Richard A. Bailey - 01242 524520

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- a) *If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.*
- b) *Write your answers in capital letters using black ink or you may type them.*
- c) *If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.*
- d) *If you have answered 'Yes' Patents Form 7/77 will need to be filed.*
- e) *Once you have filled in the form you must remember to sign and date it.*
- f) *For details of the fee and ways to pay please contact the Patent Office.*

SAFETY HELMET

This invention relates to a safety helmet.

Safety helmets are commonly worn by, for example, horse riders, cyclists and motor cyclists, with the aim of reducing injury to the wearer's head in the event that he falls, crashes or, for horse riders, is thrown. Safety helmets are also commonly worn when participating in certain other sports or activities. A typical safety helmet design incorporates a layer or pieces of a compressible or deformable material located such that, in the event of the wearer's head impacting upon an object, or an object hitting the helmet, the compressible or deformable material will deform to absorb at least some of the impact forces thereby lessening the risk of injury to the wearer. As the deformation of the compressible or deformable material can be permanent, it is usually recommended that after such an impact has occurred, the helmet is disposed of as its ability to absorb future impact forces may be reduced. Alternatively, the helmet may be repaired.

Although disposal or repair is recommended, there are often situations where the wearer may consider the impact to be of insufficient severity to require the helmet to be replaced or repaired, and so a helmet may be used which is not capable of serving its intended purpose. There are also situations where helmets are shared or used by a number of individuals none of whom may know whether an impact has

occurred whilst the helmet was being used by another. It is an object of the invention to provide a helmet user with the ability to determine the impact history of a helmet. One way of achieving this is to provide a mechanism whereby a record can be kept of the impacts experienced by a helmet.

5 According to one aspect of the invention there is provided a helmet comprising an impact sensor and a memory arranged to store impact data from the impact sensor.

It will be appreciated that by appropriate interrogation of the memory, a user can determine whether or not the helmet has been involved in an impact of
10 magnitude sufficient to impair the subsequent performance thereof.

The memory may be arranged to store the impact information in a range of ways. For example, it may record the time and magnitude of each impact experienced by the helmet. Alternatively, some form of filtering may be applied so that only data representative of impacts exceeding a pre-determined threshold value
15 are recorded. Although the time of the or each impact may be recorded, there may be occasions when this information is not required and so this data may not be stored. In a simple embodiment, the memory may be bistable and arranged to switch between a first, normal, state and a second, warning, state upon the occurrence of an impact greater than a pre-determined value.

The helmet may further include a warning device adapted to be controlled using the data stored in the memory.

For example, a warning may be triggered in the event that an impact is sensed the magnitude of which is greater than a predetermined threshold.

- 5 The predetermined threshold may be set by, for example, the helmet manufacturer, so as to be tailored to, for example, the helmet design and the intended use thereof.

The warning preferably comprises a visible warning, for example an appropriately controlled liquid crystal display. Alternatively, a warning light, for
10 example an LED arranged to be illuminated in the event of the occurrence of a large impact, may be provided. However, other warnings could be used. For example, a light may be switched off in the event of an impact, rendering the helmet fail-safe. Another possibility is to provide an audible warning.

- The impact sensor may take a range of forms. In one arrangement it
15 comprises a layer of a material sensitive to the occurrence of an impact.

The said layer of material may be incorporated into the helmet but could, alternatively, be retrofitted thereto, if desired. Where intended to be retrofitted, the layer may be fitted by, a manufacturer or repairer. Alternatively, a suitable kit may be supplied to allow the user to fit the layer to the helmet.

The layer of material conveniently comprises a layer of quantum tunnelling composite material. The electrical insulating/conducting properties of such a material vary when the material is pressed, squashed, twisted or stretched thus by measuring the electrical resistance across the layer, a measurement of whether or not an impact is occurring and the magnitude of any such impact can be made. The material may be in sheet form or alternatively may comprise granules mixed with and incorporated into the material of part of the helmet. The layer is preferably continuous, but could alternatively be discontinuous, for example in the form of a plurality of isolated regions or pads.

10 Although the sensor may take the above described form, it will be appreciated that this need not be the case and a range of other sensors could be used.

Although the provision of a suitable sensor and memory allows a user, by appropriate interrogation of the memory, to ascertain information relating to impacts experienced by a helmet and thus determine whether or not he considers it to be safe for use, it will be appreciated that other techniques are possible.

In accordance with another aspect of the invention, therefore, there is provided a helmet, and means associated with the helmet capable of providing an indication of the impact history of the helmet.

The means may take the form of a sensor and memory as described

hereinbefore. Alternatively, the means capable of providing an indication could comprise a component the state of which will change in the event of an impact exceeding a pre-determined threshold, the state of the component being apparent to a user of the helmet. By way of example, the component may be arranged to change colour in the event of a large impact, the change of colour providing an indication to a user that the helmet has been involved in an impact. Alternatively, the component may be designed to break, crack, shatter or otherwise deform in the event of an impact in such a manner as to provide an indication that an impact has occurred. Preferably the component is encased, for example within or behind a suitable transparent material layer, so as to be contained but visible to a user. Another possibility is to provide one or more reservoirs containing an ink or dye in the helmet, the reservoirs being arranged to rupture, break, leak or overflow in the event of an impact, the escaped ink or dye providing an indication to a user of the helmet's involvement in an impact.

15 The invention will further be described, by way of example, with reference to the accompanying drawings, in which:

Figures 1 and 2 are views illustrating helmets in accordance with embodiments of the invention.

Figure 1 illustrates a helmet of the type commonly worn by motor cyclists

which comprise an outer shell 10, an impact absorbing layer 12 and an inner liner 14. Between the liner 14 and the layer 12 is a layer 16 of a compressible material intended to improve the fit of the helmet on the wearer and to improve comfort. Although a range of different materials may be used in the helmet, the shell 10 is typically of a plastics material, for example a fibre reinforced plastics material. The impact absorbing layer 12 is typically of a cellular material, for example a foamed plastics material. The layer 16 may be of urethane foam.

When the wearer of the helmet experiences an impact which, in the absence of the helmet would be an impact to the head, the impact absorbing layer 12 deforms, thereby absorbing at least some of the impact force and reducing the risk of injury to the wearer.

In accordance with the invention, in order to allow monitoring of the occurrence of such impacts, an impact sensor in the form of a layer 18 of a material sensitive to the occurrence of such impacts is provided. In the arrangement illustrated the layer 18 is located between the outer shell 10 and the impact absorbing layer 12. It will be appreciated, however, that the layer may be provided elsewhere, for example on the outside of the outer shell 10.

The layer 18 is formed from a so-called quantum tunnelling composite material. Such material has the quality that its electrical resistance varies as the

mechanical load applied thereto varies. The electrical resistance across the layer 18 is, under normal circumstances, high. However, in the event of an impact resulting from, for example, the wearer being involved in a road traffic accident and his head impacting upon the road surface or another hard object, the impact force will temporarily squash or compress the layer 18 thus causing a temporary reduction in the electrical resistance across the layer 18.

The top, rear part of the helmet is shaped to define a projection 20 adapted to house a monitoring unit 22. The unit 22 is an electronic unit arranged to monitor the electrical resistance across the layer 18. This may be achieved by providing electrically conductive layers on each major surface of the layer 18, the conductive layers being isolated from one another by the layer 18, and by providing electrical connections between the unit 22 and the conductive layers, the unit 22 monitoring the electrical resistance between the connections using any suitable circuitry. The unit 22 includes a storage device or memory which is used to store data representative of the measured resistance values, and hence of the impact state of the helmet, over time. It will be appreciated, therefore, that by appropriate interrogation of the storage device, a history of events or impacts experienced by the helmet can be derived. Such interrogation may be achieved by connecting a suitable device to the unit 22 to download data from the storage device.

In addition to storage of the resistance data, the unit 22 is arranged to compare the resistance data with a stored threshold value to determine whether or not an impact has occurred of a magnitude sufficient to render the helmet unsuitable for further use. The stored threshold value may be set by the helmet manufacturer
5 and will depend, to some extent, upon the helmet design and the intended use thereof. In the event that the comparison of the resistance data with the stored threshold indicates that the helmet has experienced an impact great enough to render the helmet unsuitable for further use, a warning is triggered. In the illustrated arrangement, the warning takes the form of a display device 24 in the form of a
10 liquid crystal display which is controlled to display a suitable message. As illustrated, the device 24 is located so as to define part of the wall of the projection 20 so as to be clearly visible. Alternatively, the warning could make use of a warning light in the form of a LED operable in the event that an impact has occurred.

15 The unit 22 conveniently includes an internal power source in the form of, for example, a battery. Obviously, where a warning light is used, there is the risk that if the battery runs flat, no warning signal is produced. It may be preferred to operate on a failsafe system whereby the impact warning is triggered by, for example, switching off (rather than on) a warning light. In the event of a flat

battery, no warning light would be illuminated, and so no impression that the helmet is safe would be given. A similar operating technique may be used where the warning is displayed on a liquid crystal display.

Further possibilities include arranging for the warning light or display to be
5 illuminated or operated only when, for example, a test button is pressed. With such an arrangement, a user could test the helmet before use and note whether or not a warning indicative of the impact state of the helmet is produced. Further, it may be possible to provide an audible warning instead of or in addition to the visible warning.

10 In the arrangement described hereinbefore, the layer 18 is a separate layer. However, this need not be the case. Quantum tunnelling composite materials are available in granular form which can be incorporated into other materials. For example, the material may be incorporated into the plastics material of the outer shell 10, if desired. Further, in the arrangement described hereinbefore the layer 18
15 is continuous, providing information relating to the occurrence of impacts on any part of the helmet. However, provided a reduction in the sensitivity of the system is acceptable, the layer 18 may be discontinuous or may comprise a number of separate sensor regions or "pads".

A further alternative arrangement is shown in Figure 2. In this arrangement,

a helmet of conventional form having a shell 10 and layer 12 is modified by the fitting thereof of a layer 18 of quantum tunnelling material and a housing 20 containing a monitoring unit 22 and warning device 24. The layer 18, unit 22 and device 24 may be permanently or semi-permanently secured in position using any
5 suitable technique, for example by a suitable adhesive, or may be removably secured to the helmet, for example using a drawstring, and operate as described hereinbefore to allow monitoring of impacts experienced by the helmet.

The helmet impact monitoring techniques described hereinbefore make use of electronic sensors and memory units, for example using solid state components.

- 10 It will be appreciated that there is a wide range of other possible ways of enabling a user to determine whether or not a helmet has been involved in an impact which could impair the impact absorbing properties thereof. For example, a number of ink or dye containing packets or cells may be incorporated into the helmet and arranged to rupture to allow the ink or dye to bleed therefrom in the event of a large impact.
- 15 The ink or dye would then provide an indication to a user that the helmet has been involved in an impact. The packets or cells could be provided at or close to the surface of the helmet or located within, for example, the shock absorbing layer thereof. Where not located at the surface of the helmet, it may be desirable to incorporate, for example, a wicking material to allow passage of the ink or dye to

a location in which it can be viewed.


Alternatively, a component may be incorporated into the helmet, the component being adapted to change state in the event of an impact, the state of the component providing an indication to the user of whether or not the helmet has been
5 involved in an impact. By way of example, the component may be of a material arranged to break, shatter, crack or otherwise deform in a noticeable manner in the event of an impact. Alternatively, the component may be arranged to undergo a change of colour in the event of an impact. In such an arrangement, it may be desirable to encase or enclose the component, for example within or beneath a layer
10 of a transparent material.

As with the electronic arrangements, the components which enable impact information presentation may be incorporated upon initial manufacture or may be subsequently added to the helmet, either by a manufacturer or by the use of, for example, a kit of components.

15 Although the description hereinbefore is primarily of a helmet intended for use in motor cycling, it will be appreciated that the invention may be incorporated into helmets intended for use in a wide variety of applications, such as horse riding, cycling, motor racing or other applications in which helmets are worn to reduce the risk of head injury.

THIS PAGE BLANK (USPTO)

1/2






Figure 2

PCT/GB2004/004229



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKewed/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.